



DESMI HELIX 160



Inventory

	Great Lakes	Québec	Atlantic	Total
Desmi Helix 160	1	-	-	1

Application

Suitable for the recovery of light to high viscosity oils. Suitable for shoreline, sheltered and open water usage. Can be deployed from the shoreline, dock and vessel of opportunity or recovery barge and may be used in conjunction with the NOFI buster system.

Description

Skimmer is equipped with a circular set of hydraulically driven brushes enabling the brushes to “grab” the oil from any side of the skimmer and pull it into the pump. The HELIX brush set enables the skimmer to operate at high pickup rates even with the heaviest oils with very little water content.

Operating Data

	<u>Desmi Helix 160</u>
Nominal recovery rate:	30 m ³ /h
De-rated recovery rate:	6 m ³ /h

Ancillaries

- Hydraulic power pack
- Remote control stand
- Hydraulic hoses
- Discharge hoses with floats

Technical Data

	<u>Skimmer head</u>	<u>Power pack</u>
Draft:	40 cm	
Weight:	180 kg / 397 lbs.	
Length:	165 cm	122 cm
Width:	185 cm	40 cm
Height:	80 cm	122 cm

ECRC~SIMEC
 Suite 1201, 275 Slater Street, Ottawa K1P 5H9
 Phone (613) 230-7369 Fax (613) 230-7344
 Web: www.ecrc-simec.ca