



LORI BRUSH SKIMMERS



Inventory

	Great Lakes	Québec	Atlantic	Total
LFS (6 Brush)	-	1	-	1
LBC (3 Brush)	-	2	-	2
LSC 4 (8 Brush)	-	-	1	1
LSC 2 (4 Brush)	2	-	1	3
Total	2	3	2	7

Application

Suitable for the recovery of medium to high viscosity oil. Suitable for shoreline, sheltered and open water usage. Depending of model can be deployed from shoreline, dock, vessel and recovery barge. Suitable to be used in cold water.

Description

An oleophilic skimmer, equipped with brushes mounted on a rotating chain. Oil is scrapped off as the bristles pass through a comb-type cleaner located at the top. Units have two to six brushes.

Operating Data

Nominal recovery rate: from 75 to 200 tons/hr
De-rated recovery rate: from 15 to 40 tons/hr

Ancillaries

Power pack
Pump
Hoses

Technical Data

	<u>LFS</u>	<u>LBC</u>	<u>LSC - 4</u>	<u>LSC - 2</u>
Length:	5.2 m (17 ft 1 in)	4.9 m (16 ft 1 in)	3.1 m (10 ft 2 in)	3.1m (10 ft 2 in)
Width:	3.6 m (11 ft 10 in)	2.6 m (8 ft 6 in)	1.3 m (4 ft 3 in)	0.75m (2 ft 4 in)
Height:	1.3 m (4 ft 3 in)	2.8 m (9 ft 2 in)	2.2 m (7 ft 3 in)	3.5m (11 ft 6 in)

ECRC~SIMEC
Suite 1201, 275 Slater Street, Ottawa K1P 5H9
Phone (613) 230-7369 Fax (613) 230-7344
Web: www.ecrc-simec.ca