



# SOLID FLOTATION BOOM



## Inventory (meters)

	<b>Great Lakes</b>	<b>Québec</b>	<b>Atlantic</b>	<b>Total</b>
GP 13 in.	366 m	-	1,220 m	1,586 m
GP 20 in.	7,542 m	2,980 m	1,500 m	12,022 m
GP 24 in.	-	20,487 m	10,057 m	30,544 m
GP 36 in.	-	2,000 m	4,953 m	6,953 m
<b>Total</b>	<b>7,908 m</b>	<b>25,467 m</b>	<b>17,730 m</b>	<b>51,105 m</b>

## Application

Oil containment boom suitable for shoreline and sheltered water. It is stored in trailers, containers and on deck of seatrucks and pontoons.

## Description

It is a general purpose boom with a solid flotation core and made of polyurethane-coated polyester fabric.

## Operating Data

Maximum current: 1.5 knots

## Ancillaries

Rope  
Anchors  
Buoys

## Technical Data

	<b><u>20 in.</u></b>	<b><u>24 in.</u></b>	<b><u>36 in.</u></b>
Boom section:	15 m (50 ft)	15 m (50 ft)	15 m (50 ft)
Boom overall height:	51 cm (20 in)	61 cm (24 in)	91 cm (36 in)
Boom freeboard:	15 cm (6 in)	20 cm (8 in)	30 cm (12 in)
Boom draft:	36 cm (14 in)	41 cm (16 in)	61 cm (24 in)

ECRC~SIMEC

Suite 1201, 275 Slater Street, Ottawa K1P 5H9

Phone (613) 230-7369 Fax (613) 230-7344

Web: [www.ecrc-simec.ca](http://www.ecrc-simec.ca)