




DISC SKIMMERS



Inventory

	Great Lakes	Québec	Atlantic	Total
T-12	1	4	2	7
T-18	1	3	3	7
Total	2	7	5	14

Application

Suitable for the recovery of light to medium viscosity oil. Suitable for shoreline and sheltered use. Can be deployed from shoreline, dock or small boat.

Description

An oleophilic disc skimmer, either equipped with a diaphragm pump, installed in the middle section (T-18) or using an external pumping mechanism (T-12). Hydraulically driven by an external power pack. The RPM of the disk is adjusted, according to the viscosity of oil, in order to minimise water pick up.

Operating Data

	<u>T-12</u>	<u>T-18</u>
Nominal recovery rate: (tons/hr)	12	18
De-rated recovery rate: (tons/hr)	2	4

Ancillaries

Hydraulic power pack – diesel
Hydraulic hoses
Discharge hoses

Technical Data

	<u>T-12</u>	<u>T-18</u>
Length:	1.2 m (3 ft. 11 in)	1.3 m (4 ft. x 3 in)
Width:	1.0 m (3 ft. x 4 in)	1.2 m (3 ft. x 11 in)
Height:	0.5 m (1 ft. x 7 in)	0.6 m (1 ft. x 11 in)
Weight:	68 kg (150 lbs)	150 kg (330 lbs)