



MINIMAX30 & LAM12WD SKIMMER



Minimax 30



LAM 12WD

Inventory

	Great Lakes	Québec	Atlantic	Total
Minimax 30	2	6	3	11
LAM 12WD	4	6	4	14
	6	12	7	25

Application

Suitable for the recovery of light to high viscosity oil. Designed to recover floating oil from harbors, estuaries, rivers or as an advancing side sweep skimmer. Suitable for shoreline and sheltered water usage. Can be deployed from shoreline, vessel or recovery barge.

Description

An oleophilic brush wheel consisting of tens of thousands of bristles provides a large surface area to attract oil. Hydraulic oil rotates the brush wheel collecting 95% oil, <5% water and the oil is scraped into a sump. An external pump moves the recovered oil to an external storage unit.

Operating Data

	<u>MM30</u>	<u>LAM12WD</u>
Nominal Recovery Rate:	30m ³ /hr	30m ³ /hr
De-rated Recovery Rate:	144m ³ /day	144m ³ /day

Ancillaries

LPP 25L or LPP30D Power Pack
 VX 100 64Q or 128Q Transfer Pump
 Hydraulic hoses 2pcs
 Product transfer hoses 1pc

Technical Data

	<u>MM30</u>	<u>LAM12WD</u>
Length:	2 m (2 ft. 10 in)	1.3 m (4 ft. 3in)
Width:	1.41 m (2 ft. 3 in)	1.34 m (4 ft. 4in)
Height:	1.64 m (1 ft. 3 in)	1.1 m (3 ft. 6 in)
Weight:	185 kg	170 kg