



# DESMI HELIX 160



## Inventory

|                 | Great Lakes | Québec | Atlantic | Total |
|-----------------|-------------|--------|----------|-------|
| Desmi Helix 160 | 1           | -      | -        | 1     |

## Application

Suitable for the recovery of light to high viscosity oils. Suitable for shoreline, sheltered and open water usage. Can be deployed from the shoreline, dock and vessel of opportunity or recovery barge and may be used in conjunction with the NOFI buster system.

## Description

Skimmer is equipped with a circular set of hydraulically driven brushes enabling the brushes to "grab" the oil from any side of the skimmer and pull it into the pump. The HELIX brush set enables the skimmer to operate at high pickup rates even with the heaviest oils with very little water content.

## Operating Data

|                         | <u>Desmi Helix 160</u> |
|-------------------------|------------------------|
| Nominal recovery rate:  | 720t/day               |
| De-rated recovery rate: | 144t/day               |

## Ancillaries

Hydraulic power pack  
Remote control stand  
Hydraulic hoses  
Discharge hoses with floats

## Technical Data

|         | <u>Skimmer head</u> | <u>Power pack</u>                      |
|---------|---------------------|--|
| Draft:  | 40 cm               | 4-stroke diesel engine, 35.8 kW (48HP) |
| Weight: | 180 kg / 397 lbs.   | 830 kg / 1829 lbs                      |
| Length: | 165 cm              | 1.22 m/ 4pi                            |
| Width:  | 185 cm              | 1.00 m/3pi 3po                         |
| Height: | 80 cm               | 1.22 m/4pi                             |

ECRC~SIMEC

Suite 1201, 275 Slater Street, Ottawa K1P 5H9

Phone (613) 230-7369 Fax (613) 230-7344

Web: [www.ecrc-simec.ca](http://www.ecrc-simec.ca)