



MINIMAX 60 SKIMMER



Inventory

	Great Lakes	Québec	Atlantic	Total
Minimax 60 W	-	1	6	7

Application

Suitable for the recovery of light to high viscosity oil. Designed to recover floating oil from harbors, estuaries, rivers and lakes. Suitable for shoreline and sheltered water usage. Can be deployed from shoreline, vessel or recovery barge.

Description

An oleophilic brush wheel, built of fibreglass with aluminium reinforcing. Hydraulic oil rotates the brush wheel collecting 95% oil, <5% water and the oil is scraped into a sump. An external pump moves the recovered oil to an external storage unit.

Operating Data

	<u>Minimax 60</u>
Nominal recovery rate:	1440 tons/day
De-rated recovery rate:	288 tons/day

Ancillaries

- Power pack (diesel) 35 kW
- External DOP 160 pump
- Hydraulic hoses
- Discharge hoses

Technical Data

	<u>Skimmer</u>	<u>Powerpack</u>
Length:	1,33 m / 4pi 4po	1.22 m / 4pi
Width:	1,05 m / 3pi 4po	1 m / 3pi 3po
Height:	0,935 m / 3pi 1po	1.22 m / 4pi
Weight:	127 kg / 280 lbs	830 kg /1829 lbs