



RO-BOOM 1500



Inventory

	Great Lakes	Québec	Atlantic	Total
Ro-Boom 1500 41"	-	-	500 m	500 m

Application

Oil containment boom for unsheltered or offshore applications.

Description

RO-Boom 1500 is a Pressure-inflatable type curtain boom manufactured from heavy duty neoprene rubber with Hypalon external skin. The boom is inflated by a blower as the boom is being deployed. RO-Boom 1500 lies completely flat when deflated allowing easy cleaning, storage, recovery and maintenance. Individual air chambers provide high integrity - even if one air chamber is deflated the freeboard is maintained by adjacent air chambers.

Operating Data

Maximum current: 1.5 knots

Ancillaries

Hydraulic reel
Power pack, diesel, 5.7 kw
Towing equipment

Technical Data

Boom section:	25 m (82 ft.)
Boom overall height:	1.04 m (3 ft. 5 in)
Boom freeboard:	0.50 m (1 ft. 7 in)
Boom draft:	0.54 m (1 ft. 9 in)
Boom weight:	105 kg per section (230 lbs)

ECRC~SIMEC
 Suite 1201, 275 Slater Street, Ottawa K1P 5H9
 Phone (613) 230-7369 Fax (613) 230-7344
 Web: www.ecrc-simec.ca