



CANFLEX SEA SLUGS



Inventory

	Great Lakes	Québec	Atlantic	Total
FCB5 (5m3)	3	4	2	9
FCB10 (10m3)	3	3	6	12
FCB25 (25m3)	6	0	1	7
FCB50 (50m3)	3	0	2	5
FCB100 (100m3)	0	7	12	19
FCB250 (250m3)	0	2	2	4
				56

Application

Flexible temporary oil storage container capable of being towed or moored. Can also be used for temporary oil storage on land.

Description

Main cylindrical bladder is used for storage of oil or other liquids. The conical ends of the Sea Slug fill with air to ensure the ends ride high on the water and maintains a streamlined shape for optimum towing speed.

Operating Data

	<u>FCB5</u>	<u>FCB100</u>
Speed, empty:	up to 6 knots	up to 6 knots
Speed, full:	up to 12 knots	up to 12 knots

Technical Data

	FCB5	FCB10	FCB25	FCB50	FCB100	FCB250
Capacity :	5T	10T	25T	50T	100T	250T
Length :	6.2m (20')	9.2m (30')	11.7m (38'5")	14.3m (47')	20m (66')	27.1m (89')
Diameter :	1.1m (3'5")	1.3m (4'2")	1.8m (5'9")	2.3m (7'5")	2.8m (4'2")	3.7m (12')
Draft(full):	0.98m (3.13')	1.16m (3.76')	2.5m (1.61')	2.06m (6.71')	2.5m (8.23')	3.31m (10.91')