







Inventory

Great Lak	kes Québec	Atlantic	Total
LFS (6 Brush)	1	-	1
LBC (3 Brush)	2	-	2
LSC 4 (8 Brush)		1	1
LSC 2 (4 Brush) 2		1	3
Total 2	3	2	7

Application

Suitable for the recovery of medium to high viscosity oil. Suitable for shoreline, sheltered and open water usage. Depending of model can be deployed from shoreline, dock, vessel and recovery barge. Suitable to be used in cold water.

Description

An oleophilic skimmer, equipped with brushes mounted on a rotating chain. Oil is scrapped off as the bristles pass through a comb-type cleaner located at the top. Units have two to six brushes.

Operating Data

Nominal recovery rate: 615t/day per brush De-rated recovery rate: 123t/day per brush

Ancillaries

Power pack Pump Hoses

Technical Data

	LFS 6 (6 Brushes)	<u>LBC3</u> (3 Brushes)	<u>LSC – 4</u> (8 Brushes)	<u>LSC – 2</u> (4 Brushes)
Length:	5.2 m (17 ft 1 in)	4.9 m (16 ft 1 in)	3.1 m (10 ft 2 in)	3.1m (10 ft 2 in)
Width:	3.6 m (11 ft 10 in)	2.6 m (8 ft 6 in)	1.3 m (4 ft 3 in)	0.75m (2 ft 4 in)
Height:	1.3 m (4 ft 3 in)	2.8 m (9 ft 2 in)	2.2 m (7 ft 3 in)	3.5m (11 ft 6 in)