



# OIL STOP BOOM



## Inventory

	Great Lakes	Québec	Atlantic	Total
Oil Stop Offshore 43"	762 m	1 524 m	1 554 m	3 840 m
Oil Stop Deep Sea 60"	250 m	750 m	-	1000 m

## Application

Oil containment boom for unsheltered or offshore applications.

## Description

Oil Stop Offshore/Deep Sea (43" or 60") is a Pressure-inflatable type curtain boom developed to provide safe, quick and efficient containment of floating oil. Made with Polyester fabric with urethane/neoprene oil resistant coating, fitted with galvanized ballast chain and stainless-steel connectors.

## Operating Data

Maximum current: 1.5 knots

## Ancillaries

Hydraulic reel  
Power pack, diesel, 5.7 kw  
Towing equipment

## Technical Data

	Oil Stop Offshore 43"	Oil Stop Deep Sea 60"
Boom section:	30 m (98 ft.)	30 m (98 ft.)
Boom overall height:	1.090 m (3 ft. 7 in)	1.524 m (5 ft.)
Boom freeboard:	0.460 m (1 ft. 6 in)	0.610 m (2 ft.)
Boom draft:	0.640 m (2 ft. 1 in)	0.910 m (3 ft.)
Boom weight:	6 kg per m (13.2 lbs)	(5.6 lbs/ft) (8.4 kg/m)