



Inventory

	Great Lakes	Québec	Atlantic	Total
36 feet		-	11	11
34 feet	2	11	-	13
32 feet	- 7 .	. 1	-	1
30 feet	6	6	-	12
Total	8	18	11	37

Application

Used mainly for deployment of boom in sheltered water or close to shoreline and for skimming operation. Also used for the transportation of personnel and equipment during shoreline clean-up operations. Having a shallow draft, they permit access to almost any shoreline. Units are road transportable, each unit having a dedicated trailer.

Description

Built of aluminum, the vessels vary in size from 30' x 10' to 36' x 12'. They are equipped with two outboard motors (135 to 200HP).

Ancillaries

Depth sounder

GPS with electronic charts

Some units fitted with radar

Operating Data

Speed: up to 30 knots Run Time: 6 hrs Road transportable

Technical Data

	<u>30 feet</u>	<u>32 feet</u>	<u>34 feet</u>	<u>36 feet</u>
Length:	9.1 m (30 ft.)	9.8 m (32 ft.)	10.4 m (34 ft.)	10.9 m (30 ft.)
Beam:	3.0 m (10 ft.)	3.7 m (12 ft.)	3.7 m (12 ft.)	3.7 m (12 ft.)
Draft:	30 cm (12 in)	30 cm (12 in)	30 cm (12 in)	40 cm (16 in)

ECRC~SIMEC Suite 1201, 275 Slater Street, Ottawa K1P 5H9 Phone (613) 230-7369 Fax (613) 230-7344 Web: <u>www.ecrc-simec.ca</u>