



GENERAL PURPOSE BOOM



Inventory

	Grands-Lacs	Québec	Atlantic	Total
GP 13 inch	366 m	366 m	1 220 m	1 952 m
GP 20 inch	7 757 m	-	-	7 757 m
GP 24 inch	-	20 496 m	9 133 m	29 609 m
GP 36 inch	-	1 996 m	4 999 m	6 995 m
Total	8 123 m	22 492 m	15 332 m	46,313 m

Application

Oil containment general purpose boom suitable for shoreline sheltered waters. It is stored in trailers, containers and on the deck of seatrucks and barges.

Description

It is a curtain type general purpose boom with a solid foam flotation core and made of polyurethane-coated and polyester fabric. They are fitted with standard quick connectors and galvanized ballast chain.

Operating Data

Maximum current: 1.5 knots

Ancillaries

Ropes
Anchors
Buoys

Technical Data

	13 inch	20 inch	24 inch	36 inch
Boom section:	15 m (50 ft.)	15 m (50 ft.)	15 m (50 ft.)	15 m (50 ft.)
Boom Overall height:	51 cm (13 in)	51 cm (20 in)	61 cm (24 in)	91 cm (36 in)
Boom freeboard:	15 cm (6 in)	15 cm (6 in)	20 cm (8 in)	30 cm (12 in)
Boom draft:	36 cm (14 in)	36 cm (14 in)	41 cm (16 in)	61 cm (24 in)

ECRC~SIMEC
Suite 1201, 275 Slater Street, Ottawa K1P 5H9
Phone (613) 230-7369 Fax (613) 230-7344
Web: www.ecrc-simec.ca